



PREMIUM FLOOR FINISH HS

LYNX PREMIUM FLOOR FINISH HS is a premium high solids floor finish with modified acrylic polymers for both low maintenance and high speed burnishing.


DIRECTIONS: 1) Thoroughly strip floor with a **LYNX FLOOR FINISH REMOVER**. 2) Rinse floor thoroughly with clean water. 3) Apply 2-4 thin uniform coats of floor finish allowing time to dry thoroughly between coats. Allow for longer drying time in damp weather. **Maintenance:** Dust mop, sweep or damp mop as needed. If desired, burnish with electrical, battery or propane high-speed buffers using a synthetic or synthetic / natural blend pad. Depending on traffic, burnish 1-3 times a week.

CAUTION: Keep out of reach of children. It is recommended that protective gloves and safety glasses be worn when using this product. Make sure there is adequate ventilation. Refer to M.S.D.S. for additional safety information.

TYPICAL PROPERTIES:

Specific Gravity:.....	1.04
Solids:.....	25%
pH:.....	8.5
James Static Coefficient of Friction:...	0.6
Leveling:.....	Excellent
Film Formation:.....	Excellent
Gloss:.....	Excellent
Water resistance:.....	Excellent
Detergent resistance:.....	Excellent
Removability:.....	Excellent
Black heel mark resistance:.....	Excellent
Odor:.....	Mild acrylic
Appearance:.....	White emulsion

Manufactured by:
ABC COMPOUNDING COMPANY, INC.
ATLANTA, GA / DALLAS, TX



FEATURES

Modified Acrylic
Polymers

Superior Gloss
And Durability

Outstanding Burnish
Response With No
Powdering Or Dusting

BENEFITS

Labor Saver Through-
Less Frequent Need To
Buff, Burnish & Re-coat,
And A Reduction In The
Number Of Strippings

WHERE TO SELL

Hospitals / Healthcare

School Systems

Grocery / Convenience
Stores

Shopping Centers / Malls

Sports Facilities

Office Buildings

Airports

www.lynxclean.com

Lynx is a Registered Trademark of
ABC Compounding Co., Inc.

LX0103/0605